# **IFCP - TIRE MARK REMOVER**

## BLACK STREAK AND TIRE MARK REMOVER

### WHERE USED:

For use on floors and equipment that commonly get marked by forklift and other vehicle tires.

### HOW USED:

Highly effective "ready to use" solution that is simply applied to black streaks and/or tire marks with a trigger or pump up sprayer. Or, for a more efficient cleaning process, spray IFCP-TMR on black streaks and/or tire marks prior to using a mop or automatic floor scrubber.

#### FEATURES:

- Effectively attacks black streaks and tire marks commonly found on interior and exterior flooring and equipment surfaces
- Free rinsing
- User friendly



| oH of Conc.                                      | 12.7 (nominal)                                                                                                                                                                                                    |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| oH of 20:1 dilution:                             | N/A                                                                                                                                                                                                               |
| olubility: Products, L.L.C.                      | Soluble in water                                                                                                                                                                                                  |
| VOC content:                                     | 0%                                                                                                                                                                                                                |
| Biodegradable:                                   | YES                                                                                                                                                                                                               |
| Jseable Temp Range:                              | Ambient – 210 F (Higher Temp = Lower Foaming                                                                                                                                                                      |
| INDUSTRIAL FLOO<br>N112 W18810 MEQUON ROAD • GEF | gallon pail, 55-gallon drum, 275-gallon tote<br>OR CARE PRODUCTS, LLC<br>RMANTOWN, WI USA 53022 • 414-448-0303<br>RCARELLC.COM                                                                                    |
|                                                  | oH of 20:1 dilution:<br>Solubility: Products LLC<br>/OC content:<br>Biodegradable:<br>Jseable Temp Range:<br>CONTAINER SIZES: 12 × 32 oz. case, 5<br>INDUSTRIAL FLOOR<br>N112 W18810 MEQUON ROAD • GEF<br>• FLOOP |